

Provided with:

- Automatic Dehumidostat
- Four pivoting wheels
- Round pipe Evaporator
- Electronic Defrosting system

Peculiarities:

- Attractive Design, absolutely silent
- Very low Power Consumption
- Available in 7 standard colours and other "custom" colours
- Ecologic Gas R134a

Used mainly in:

- All humid damp places
- Laundries bathrooms, cellars
- Flats, sea houses, basements
- Libraries, museums etc.

Voltage Available:

- 230/1/50 230/1/60
- 115/1/50 115/1/60



FLIPPERDRY

Data Sheet Flipper Dry. GB V2 12.05

CONDENSED WATER AT DIFFERENT AMBIENT TEMPERATURE AND HUMIDITY CONDITIONS

Mod.	10°C 60%	10°C 80%	15°C 60%	15°C 80%	20°C 60%	20°C 80%	25°C 60%	25°C 80%	27°C 65%	27°C 80%	30°C 80%	32°C 90%
F300	2 l/24h	5 l/24h	3 l/24h	6 l/24h	5 l/24h	7 l/24h	7 l/24h	10 l/24h	8.5 l/24h	12 l/24h	15 l/24h	19 l/24h
F400	3 l/24h	7 l/24h	5 l/24h	9 l/24h	6 l/24h	11 l/24h	9 l/24h	14 l/24h	10,5 l/24h	15 l/24h	19 l/24h	24 l/24h

TECHNICAL DATA:	F300	F400
Rated Aver. Power Consumpt. (at 20°C, 60% R.H.)	250 W	330 W
Max Power Consumption (at 35°C, 95% R.H.)	320 W	410 W
Max. Absorbed Current (at 35°C, 95% R.H.)	1.9 A	2,5 A
Air Flow	250 cm/h	300 cm/h
Suond Pressure Level (at 3 mts in free field)	39 db(A)	41 db(A)
Refrigerant R134a	235 g	205 g
Defrosting Control System	electronic	
Capacity of Condensed Water Tank	5,5 liters	5,5 liters
Functioning Temp. Range	7-35 °C	7-35 °C
Functioning Relative Humidity Range	35 - 99 %	35 - 99 %
Rated Condensation Capacity (at 30°C 80%)	15 l/24h	19 l/24h
Rated Condensation Capacity (at 32°C-90%)	19 l/24h	24 l/24h
Weight with empty tank	23 kg	23 kg
Dimensions with LxDxH mm	350x320x700	
Dimensions of the Packaging Carton Boxes LxDxH mm	430x370x780	
Number of Units in 40' (20') container	480 (234)	

