

Provided with:

- Electronic Control
- Display with all indications of temperature and Relative Humidity
- Provided with Ionizer-6 KV

Peculiarities:

- Futuristic: elegant and refined design
- Round smooth not finned pipe Evaporator
- Three speed fan
- Low Power Consumption
- Available in many colours (Metal Grey, Anthracites, White, etc.)

Used mainly in:

- Houses, Kitchen
- Laundries
- Shops
- Libraries

Voltage Available:

- 230/1/50 230/1/260
- 115/1/50 115/1/60



Cobra

Data Sheet Cobra V.3 09.06

TECHNICAL DATA:	Cobra
Rated Maximum Power absorbed (at 20°C, 60% R.H.) with ionizer	205 W
Rated Maximum Power absorbed (at 35°C, 95% R.H) with ionizer	320 W
Max. Current Absorbed (at 35°C, 95% R.H)	2.2 A
Air Flow	250 cm/h
Sound Pressure Level (at 3 mts in free field)	39 db(A)
Refrigerant R134a	160 g
Defrosting Control System	electronic
Capacity of Condensed Water Tank	4 liters
Functioning Temperature Range	6-35 °C
Functioning Relative Humidity Range	35 - 99 %
Rated Condensation Capacity (at 30°C - 80 %)	14 l/24h
Rated Condensation Capacity (at 32°C-90 %)	18 l/24h
Weight with empty tank	16.5 kg
Dimensions LxDxH mm	330x320x600
Dimensions with Packaging Carton Boxes LxDxH mm	355x366x653
Number of Units in 40' (20') container	approx. 600 (280)

